

### IMPORTANT SAFETY INSTRUCTIONS

for

Roller Screen, Wind Resistant - CHAIN OPERATION

# PLEASE READ THESE INSTRUCTIONS CAREFULLY BEFORE Installing the Roller Screen, Wind Resistant with Chain Operation.

#### **CHILD SAFETY WARNING:**

- Young children can be strangled by loops in cords and chains that operate this screen.
- Children can be strangled if the device is not installed correctly.
- Move beds, cots and furniture away from windows where chain operated blinds are fitted.
- Keep the instructions for future reference.

## Your screen has been fitted with a new safety device: 2 part Clear Chain Safety Breakaway (Decorquip part number 400982)

(This replaces the black 3 ball chain connector as shown in the fitting instruction diagrams) The Clear Chain Safety Breakaway device has been tested in accordance with BS EN 16434: 2014 Internal Blinds, Clause 7.

The Clear Chain Safety Breakaway consists of two parts that are joined together (see diagram).



- WITH the new safety breakaway fitted the bottom of the chain loop must be MINIMUM 60cm from the ground.
- (WITHOUT the breakaway fitted the bottom of the chain loop must be MINIMUM 1.5m from the ground and must run through a safety clip).
- The chain length should be 2/3rds of the height of the screen.
- Remove excess chain if necessary. Clip each part of the clear breakaway connector to each end of the chain, positioning the connector just below the chain mechanism in the cassette.
- Check that the chain is running smoothly through the end cap and the screen is operating correctly.
- TO OPERATE THE SCREEN PULL THE CHAIN FROM ABOVE THE SAFETY BREAKAWAY DEVICE

#### **WARNINGS**

- Test the connector if not used regularly
- Replace the connector if faulty
- The release of small components can result in asphyxiation of small children.
- Use of additional safety devices helps reduce the risk of strangulation but cannot be considered entirely fool-proof.

If you have any questions please call The Flyscreen Company 01454 238288 or email enquiries@flyscreen.com