

PVC Strip Curtain



Keep insects out. Let fresh air in.

A durable and practical solution for commercial doorways, designed to help reduce the entry of insects, birds, dust and draughts whilst still allowing easy access for staff, pallet trucks and forklifts. Clear PVC strips provide excellent visibility and flexibility, making them ideal for warehouses, kitchens, workshops and industrial environments.

Why Choose This Screen?

The individual PVC strips hang from a high-quality stainless steel rail, creating a flexible barrier that is easy to pass through whilst helping to maintain airflow separation between areas. The strips can be removed individually for cleaning or replacement, and the overlap can be adjusted during installation to suit the application.

Suitable for both internal and external commercial doorways, the system is available with either standard grade PVC or polar grade PVC for colder environments.

Product Details

- Clear PVC strip panels
- Stainless steel hook-on rail system
- Suitable for pallet truck and forklift access
- Choice of standard grade PVC (0°C) or polar grade PVC (-25°C)
- Made-to-measure and supplied ready to fit
- Individual strips can be removed or replaced if required
- Compatible with commercial mesh panels with metal headings



Before You Order

Please ensure there is enough flat fixing surface around the doorway for the rail and curtain overlap. For face fixing, we recommend allowing at least 25mm of flat surface on each side of the opening, although wider overlaps may be beneficial for larger openings or exposed areas. Check for any obstructions such as pipework, handles, trunking or uneven wall surfaces before ordering.

Turn over for the step-by-step measuring guide.

The Flyscreen Company Ltd, Unit 4, Warren Business Park, Knockdown, Tetbury, Gloucestershire, GL8 8QY

sales@flyscreen.com | 01454 238288 | www.flyscreen.com

Company Register: 3615661 | VAT: 741888897

Fly Screen Systems | Insect Mesh | Soffit & Ventilation Mesh | Chain Screens | Electric Fly Killers | Pest Control Options

September 2026

PVC Strip Curtain



Measuring Instructions

Step 1: Measure the Width

Measure the full width of the aperture, including any bevelled edges around the frame.

For face fixing, allow at least 25mm overlap each side of the opening.

For wider openings or external fitting, a larger overlap of 50mm or more per side may be preferable.

Step 2: Measure the Height

Measure from the top of the door frame down to the floor or threshold.


Deduct 10mm to provide floor clearance once fitted.

Step 3: Final Order Size


Width = Aperture width + 25mm left overlap + 25mm right overlap

Height = Aperture height - 10mm


Stainless Steel Rail



Profile and dimensions



Face fit



Reveal fit



Important Notes

- Always measure in millimetres (mm) and provide sizes as width × height
- Include any bevelled edges in your measurements
- All screens are made to your measurements (±2mm tolerance applies), so it's important to measure carefully.
- No allowances or deductions are made by us
- Double check your measurements before ordering

*Stainless steel hooks are spaced at 41mm intervals, so the rail can only be cut between hook centres. If we are unable to cut the rail to the exact size ordered, it will be supplied to the next largest complete hook spacing. If required, the rail can be trimmed further on site using a hacksaw.